

deliveries of gas hereunder, but such equipment shall be adjusted at once to read accurately. If, upon test, the measuring equipment shall be found to be inaccurate in the aggregate by an amount exceeding two percent (2%) at a reading corresponding to the average rate of flow for the period since the last preceding test, then any previous readings of such equipment shall be corrected to zero error for any period which is known definitely or agreed upon. But in the case the period is not known definitely or agreed upon, such correction shall be for a period extending over one-half of the time elapsed since the date of the last test.

(h) The First Party shall have the right to be represented at and to participate in all tests of gas delivered hereunder or of any equipment used in measuring or determining the nature or quality of such gas and to inspect at any time during business hours, any and all equipment used for the measurement or determination of the nature or quality of gas delivered hereunder, but the reading, calibrating and adjustment thereof, and the changing of charts, shall be done only by employees, agents, or representatives of Second Party.

(i) The deviation of the gas from Boyle's Law at the pressures and temperature under which the gas is delivered by First Party to Second Party hereunder shall be determined by joint tests at intervals of six (6) months, or as much oftener as is found necessary in practice. The apparatus and the method to be used in making said tests shall be in accordance with the recommendations of the National Bureau of Standards of the Department of Commerce or by other method as may be mutually agreed upon. Each test shall determine the corrections to be used in computations for the measurement of natural gas deliveries hereunder until the next test.